

## **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

### **Listing of Claims**

**Claim 1 (Currently amended):** A portable terminal apparatus for displaying information on a plurality of display surfaces provided on front and back surfaces of a casing by using a single liquid crystal display device, comprising:

a light guide plate, which guides illuminating lights from a light emitting element of the single liquid crystal display device to opposite directions to each other to irradiate both surfaces of a main body part of the liquid crystal display device with the lights; and

a detecting unit, which detects opening and closing operations of the casing,  
wherein an operating area of the liquid crystal display device is limited in  
accordance with the opening and closing states detected by the detecting unit to  
switch the display part for displaying the image information.

**Claim 2 (Original):** The portable terminal apparatus as set forth in claim 1, wherein a single light guide plate is provided so as to extend until both the surfaces of the main body part of the liquid crystal display device to irradiate both the surfaces of the main body part of the single liquid crystal display device with the lights.

**Claim 3 (Original):** The portable terminal apparatus as set forth in claim 1, wherein the light guide plate is formed in a winding shape on both the surfaces of the main body part of the liquid crystal display device to irradiate both the surfaces of the main body part of the single liquid crystal display device with the lights.

**Claim 4 (Previously presented):** The portable terminal apparatus as set forth in claim 1, wherein an opening is formed on a part of the light guide plate facing the main body part of the liquid crystal display device; and

wherein the opening allows to visually recognize display image information therethrough.

**Claim 5 (Original):** The portable terminal apparatus as set forth in claim 4, wherein transmitting areas corresponding to the display surfaces through which the illuminating lights can be transmitted in both the surfaces of the main body part of the liquid crystal display device are provided at positions shifted to each other to avoid an overlap; and

wherein the opening of the light guide plate is provided at the position corresponding to the transmitting area of the main body part of the liquid display device.

**Claim 6 (Canceled)**